



L&R Manufacturing Company
577 Elm Street, P.O. Box 607, Kearny, New Jersey 07032-0607 USA
Phone: 201-991-5330, Fax: 201-991-5870
E-mail: info@LRultrasonics.com, www.LRultrasonics.com

TOUCHTONE CONTROLS

Now, instead of scrubbing touchtone controls by hand, all you need to do is place them in an L&R Ultrasonic Cleaning system and flip the switch. Then sit back and watch the machine do the work for you. Simply-

1. Fill the first tank about 3/4 full with #222 Non-Ammoniated Ultrasonic Instrument Cleaning Solution.
2. Place the Basket containing parts (numbers down) in the first tank and cavitate 6-12 minutes.
3. Lift Basket and place into second tank containing Instrument Rinsing Solution and cavitate 6-12 minutes.
4. Remove parts and air dry.

EQUIPMENT NEEDED:

Machines & Accessories*: Q210 Ultrasonic Cleaning System with Timer, Basket, Auxiliary Pan.

Solutions: #222 Non-Ammoniated Ultrasonic Instrument Cleaning Solution (Product Code 191); or Instrument Rinsing Solution (Product Code 194).

*Recommended Ultrasonic Cleaning System varies as to internal tank dimensions and volume of required cleaning.

APPLICATION BULLETIN #49